

Electric Chain Hoist Stainl. Steel Zone 22 / Atex II 3 D

Technical Details:

SKC 080.22-FNUex - Electric Chain Hoist Stainl. Steel Ch.

Body size	10
Trolley type	Motor-trolley FNU
Safe working load (kg)	1000
Duty class	ISO M3 (FEM 1Bm)
Falls	2
Lifting Height (m)	10
Hoisting speed Low (m/min)	1.0
Hoisting speed High (m/min)	4.0
Hoist motor power (kW)	1,7/0.4, 40% ED
Power supply (V)	400
Frequency (Hz) 50	
Phase 3	
Control voltage (V)	48
Hoisting limit switch	With upper and lower limit switch
Trolley speed Low (m/min)	5
Trolley speed High (m/min)	20
Travelling acceleration time	2.5 s
Trolley travel control method	Two step with ramps
Travel motor type	Frequency converter motor
Travelling gear type	GEL
Width for flange (mm)	200
Contact control	
Protection	AREA22
Stainless steel load chain	
Chain container	
Slipping clutch	
CE-sign	
Normal indoor use	
Temperature -20 ... +40C	
Travelling limit switch	One Step
Food lubricant to grease the chain	Yes
Zone 22 / Atex II 3 D	Yes
Thermal motor protection hoisting	Yes
Thermal motor protection travelling	Yes
Rain covers (hoist)	Yes
Rain covers (motor trolley)	Yes
Increased protection hoist (outdoor use)	Yes
Increased protection trolley (outdoor use)	Yes
Language of documents	EN (English)
Document type	Paper
Number of documents	1

Please contact:

Verena Eder

Order Processing Manager

Email: verena.eder@swfkrantechnik.com